








PRODUCT DATASHEET



OX-ON Worker | Comfort 2306

- Welding glove
- Cotton lining provides good comfort
- Heat-resistant effect
- Suitable as a barbecue glove



CATEGORI	EN-STANDARD																																
 CAT II	<table border="1"> <tr> <td colspan="2">EN388:2016</td> <td colspan="2">EN407:2004</td> <td rowspan="2">EN12477:2001 EN 12477 A</td> </tr> <tr> <td></td> <td> <table border="1"> <thead> <tr> <th></th> <th colspan="2">Level</th> </tr> </thead> <tbody> <tr> <td>Abrasion resistance</td> <td>4</td> <td>1-4</td> </tr> <tr> <td>Blade cut resistance</td> <td>1</td> <td>1-5</td> </tr> <tr> <td>Tear resistance</td> <td>3</td> <td>1-4</td> </tr> <tr> <td>Puncture resistance</td> <td>3</td> <td>1-4</td> </tr> <tr> <td>TDM Cut resistance</td> <td>X</td> <td>A-F</td> </tr> </tbody> </table> </td> <td></td> <td> 4 Burning behaviour 2 Contact heat 2 Convective heat 3 Radiant heat 4 Small splashes of molten metal X Large quantities of molten metal </td> </tr> <tr> <td></td> <td>4133X</td> <td>42234X</td> <td></td> <td></td> </tr> </table>	EN388:2016		EN407:2004		EN12477:2001 EN 12477 A		<table border="1"> <thead> <tr> <th></th> <th colspan="2">Level</th> </tr> </thead> <tbody> <tr> <td>Abrasion resistance</td> <td>4</td> <td>1-4</td> </tr> <tr> <td>Blade cut resistance</td> <td>1</td> <td>1-5</td> </tr> <tr> <td>Tear resistance</td> <td>3</td> <td>1-4</td> </tr> <tr> <td>Puncture resistance</td> <td>3</td> <td>1-4</td> </tr> <tr> <td>TDM Cut resistance</td> <td>X</td> <td>A-F</td> </tr> </tbody> </table>		Level		Abrasion resistance	4	1-4	Blade cut resistance	1	1-5	Tear resistance	3	1-4	Puncture resistance	3	1-4	TDM Cut resistance	X	A-F		4 Burning behaviour 2 Contact heat 2 Convective heat 3 Radiant heat 4 Small splashes of molten metal X Large quantities of molten metal		4133X	42234X		
EN388:2016		EN407:2004		EN12477:2001 EN 12477 A																													
	<table border="1"> <thead> <tr> <th></th> <th colspan="2">Level</th> </tr> </thead> <tbody> <tr> <td>Abrasion resistance</td> <td>4</td> <td>1-4</td> </tr> <tr> <td>Blade cut resistance</td> <td>1</td> <td>1-5</td> </tr> <tr> <td>Tear resistance</td> <td>3</td> <td>1-4</td> </tr> <tr> <td>Puncture resistance</td> <td>3</td> <td>1-4</td> </tr> <tr> <td>TDM Cut resistance</td> <td>X</td> <td>A-F</td> </tr> </tbody> </table>		Level		Abrasion resistance	4	1-4	Blade cut resistance	1	1-5	Tear resistance	3	1-4	Puncture resistance	3	1-4	TDM Cut resistance	X	A-F		4 Burning behaviour 2 Contact heat 2 Convective heat 3 Radiant heat 4 Small splashes of molten metal X Large quantities of molten metal												
	Level																																
Abrasion resistance	4	1-4																															
Blade cut resistance	1	1-5																															
Tear resistance	3	1-4																															
Puncture resistance	3	1-4																															
TDM Cut resistance	X	A-F																															
	4133X	42234X																															

MATERIALS
70% Leather 30% Cotton

PREPACKAGING / MIN. SALESQUANTITY
36 pair per. Colli / 6 pair per. Bag

ART no.	EAN	DB	FINFO	SIZE
125.50	5701952125500	3115268	4529946	10
125.52	5701952125524	1455682	6750925	12

SHORT DESCRIPTION

OX-ON Worker Comfort 2306 is perfect for CO2 welding or heavier industrial work—or as a great barbecue glove.

Split leather on the back of the hand and palm makes the glove resistant to sparks and heat.

The glove is provided with a cotton liner for extra flexibility and comfort.